

HP Everyday Adhesive Gloss Polypropylene, 2 Pack



The HP Designjet printing system—the complete solution

HP Designjet printers, Original HP inks and printheads, and Original HP printing materials are designed to work together as a system to provide reliable, consistent results with every print.



1 With Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series. Display permanence rating for interior displays/ away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see <u>HPLFMedia.com/hp/t/</u> printpermanence.

Get brilliant results with an easy-to-handle film

Achieve accurate photo reproduction, crisp detail

Produce POP, retail, and event displays full of vibrant color and brilliant, photo-realistic images. Together with Original HP inks, this material gives you a wide color gamut and excellent gloss uniformity for smooth transitions and crisp detail.

Gain efficiency

Help keep your production process moving smoothly. Instant-dry, smudge-resistant prints are easy-to-handle and feature a permanent self-adhesive for secure, reliable mounting.

Offer a range of indoor and outdoor displays

Take advantage of this versatile material, compatible with both HP dye- and pigment-based inks. ICC profiles help you get the right color, right away. Indoor prints provide over 35 years unlaminated display permanence.²

Target customers	Applications	Benefits	
Commercial print service providers	POP and retail displays	Vibrant color, excellent gloss uniformity	
Quick printers	Trade show and event displays	Brilliant, photo-realistic images enabled by excellent bleed control	
Copy shops	Temporary exhibitions	A permanent self adhesive for secure, reliable mounting	
Architects	Architecture competitions	Easy-to-handle, instant-dry, smudge-resistant prints	
		35+ years unlaminated indoor display permanence on HP Designjet Z-series printers ¹	
		Compatible with both HP dye- and pigment-based inks	
		Indoor and outdoor application versatility	

Technical specifications



HP Everyday Adhesive Gloss Polypropylene, 2 Pack

For the latest ICC profiles/paper presets, please visit <u>HPLFMedia.com/hp/paperpresets</u>.

Weight (without liner)	120 g/m² per ISO 536 Test Method	120 g/m² per ISO 536 Test Method				
Weight (with liner)	185 g/m² per ISO 536 Test Method					
Thickness (without liner)	180 microns/7.1 mil per ISO 534 Test Method					
Thickness (with liner)	215 microns/8.5 mil per ISO 534 Test Method					
Opacity (with liner)	Greater than 95% per TAPPI T-425 Test Method, greater than 96% per ISO 2471 Test Method					
Brightness (with liner)	87.5% per TAPPI T-452 Test Method, 90% per ISO 2470 Test Method					
Whiteness (with liner)	97 per ISO 11476 and ISO 11475 Test Methods					
Finish	Gloss					
Operating temperature	15 to 35° C / 59 to 95° F					
Operating humidity	20 to 80% RH					
Display permanence	75+ years, unlaminated with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70					
(Indoor home or office)	Photo Inks on the HP Designjet Z3200 Photo Printer series ³					
Water resistance	Moderately water resistant with Original HP 771 Vivid Photo Inks, Original HP 91 Photo Inks, or Original HP 70 Photo Inks on the HP Designjet Z3200 Photo Printer series, ⁴ lamination recommended with Original HP dye inks					
Dry time	1 minute (at 23° C, 50% RH)					
Lamination	Yes					
Shelflife	2 years, unopened in original packaging					
Storage temperature	15 to 35° C / 59 to 95° F					
Storage humidity	15 to 30% RH					
Country of origin	Product of China					
Ordering information	Product numbers Quantity Roll sizes	UPC Codes	Region			
	COF28A 2 Pack 914 mm x 22,9 m (36 in x 75	t) 848412012910	Worldwide			
	COF29A 2 Pack 1067 mm x 22,9 m (42 in x 75	ft) 848412012927	Europe, Americas			
Warranty	HP large format printing materials are free from defects in r statement please see <u>HPLFMedia.com/hp/MediaWarranties</u> customer support at <u>HPLFMedia.com/hp/en/contactus</u> .		,			



- ³ Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see HPLFMedia.com/hp/printpermanence.
- ⁴ Water resistance testing by HP Image Permanence Lab on a range of HP media and follows ISO 18935 method. For more information, see <u>HPLFMedia.com/hp/</u> printpermanence.

For detailed information on the HP large format printing materials portfolio and to order, see HPLFMedia.com

© 2021 HP Development Company, L.P. © 2021 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

