

HP Heavyweight Coated Paper



The HP DesignJet printing system—the complete solution

HP DesignJet printers, Original HP inks and printheads, Original HP printing materials and HP Scitex printers, are designed to work together as a system to provide reliable, consistent results with every print.



Accomplish more with consistent results

Produce high-quality, fast-drying results

Roll or stack your time-sensitive documents right off the printer. Ideal for rich, color-accurate prints, working comps, and design proofs, this heavyweight paper is easy to handle and provides high-quality, consistent results. From line drawings to illustrations and light ink-density graphics, see high-quality, consistent image quality print to print and roll to roll.

Improve your response time

Handle prints with confidence right off the printer. An enhanced coating provides ink abrasion resistance to help you deliver on quick turnaround times.

Do more, with the environment in mind

Gain versatility with this premium bright white paper. From working comps and design proofs to fine line drawings and illustrations, meet the project needs and the environmental objectives of your company and clients with this recyclable paper,¹FSC[®]-certified paper.²

Target customers	Applications	Benefits	
Architects	Posters and presentations	Rich, color-accurate prints and consistent, high-quality results	
Engineers	POP and retail displays Resistance to ink abrasion handling		
Geographic Information Systems (GIS) professionals	Geographic Information Systems (GIS)	100+ years display permanence indoor²; in-window 3 months unlaminated, 2 years laminated³	
Graphic designers	Architecture (AEC) and engineering (MCAD)	Recyclable through commonly available program ¹	
Print service providers		FSC®-certified paper. ⁴	



Technical specifications

HP Heavyweight Coated Paper

For the latest ICC profiles/paper presets, please visit <u>HPLFMedia.com/paperpresets</u>.

Weight	130 g/m² per IS	130 g/m² per ISO 536 Test Method, (35 lbs)					
Thickness	167 microns/6.	167 microns/6.6 mil per ISO 534 Test Method					
Opacity	96% per TAPPI	96% per TAPPI T-425 Test Method					
Brightness	89% per TAPPI	89% per TAPPI T-452 Test Method					
Whiteness	144 per CIE Gar	144 per CIE Ganz 82 Test Method					
Finish	Matte	Matte					
Operating temperature	15 to 35° C / 59	15 to 35° C / 59 to 95° F					
Operating humidity	20 to 80% RH	20 to 80% RH					
Display permanence (Indoor home or office)	100+ years with Original HP 83 UV inks ²						
Display permanence (Commercial in-window)	3 months unlan	3 months unlaminated, 2 years laminated with Original HP 91 Photo Inks ³					
Dry time	Immediate (at 2	Immediate (at 23° C, 50% RH)					
Shelf life	1 year, unopene	1 year, unopened in original packaging					
Storage temperature	0 to 40° C / 32 t	0 to 40° C / 32 to 104° F					
Storage humidity	5 to 95% RH	5 to 95% RH					
Environmental	Recyclable thro	Recyclable through commonly available recycling programs 1 and FSC $^{\odot}$ -certified. 4					
Country of origin	Product of Gern	Product of Germany					
Ordering information	Product numbers	Roll sizes	UPC Codes	Region			
	C6029C	610 mm x 30,5 m (24 in x 100 ft)	848412013108	North America, Europe, Asia			
	C6030C	914 mm x 30,5 m (36 in x 100 ft)	848412013115	Worldwide			
	C6569C	1067 mm x 30,5 m (42 in x 100 ft)	848412013122	Worldwide			
	C6570C	1372 mm x 30,5 m (54 in x 100 ft)	848412013146	North America, Europe, Asia			
	C6977C	1524 mm x 30,5 m (60 in x 100 ft)	848412013153	Worldwide			
	Q1956A	1067 mm x 67,5 m (42 in x 225 ft)	848412013139	North America, Europe			
	Q1957A	1524 mm x 67,5 m (60 in x 225 ft)	848412013160	North America, Europe			
Warranty	statement, plea	HP large format printing materials are free from defects in materials and workmanship. For warranty statement, please see <u>HPLFMedia.com/mediawarranties</u> . To obtain warranty service, please contact Brai Management Group customer support at <u>HPLFMedia.com/hp/en/contactus</u> .					

¹ HP Large Format Media take-back program availability varies. Some recyclable HP papers can be recycled through commonly available recycling programs. Recycling programs may not exist in your area. See HPLFMedia. com/hp/ecosolutions for details.

² Display permanence rating for interior displays/away from direct sunlight, under glass by HP Image Permanence Lab and/or by Wilhelm Imaging Research, Inc. on a range of HP media. For more information, see HPLFMedia. com/printpermanence.

³ Interior in-window display ratings by HP Image Permanence Lab on a range of HP media. HP predictions based on test data under Xenon-Arc illuminant—calculation assumes 6,000 Lux/12 hr day. For more information, see HPLFMedia.com/printpermanence.

BMG trademark license code FSC®-C115319, see fsc.org. HP trademark licence code FSC®-C017543, see fsc.org. Not all FSC®-certified products are available in all regions. For information about HP large format printing materials, please visit HPLFMedia.com.



For detailed information on the HP large format printing materials portfolio and to order, visit HPLFMedia.com

© 2017 HP Development Company, L.P. © 2017 Brand Management Group. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP and BMG shall not be liable for technical or editorial errors or omissions contained herein.

HP is a registered trademark of HP Development Company, L.P. and is used by Brand Management Group on license from HP Development Company, L.P.

