

Technical Specifications

FibaPrint® Ultra Smooth Gloss 285gsm

Photo Art Range IFA 49

Product Description

High white, ultra smooth gloss archival quality digital fine art paper with crystal layer technology, compatible with aqueous pigment and dye inkjet printers.

Features

- Crystal layer technology, unique to FibaPrint®
- · High white
- Fibre based photo quality
- Archival acid and lignin free
- Aqueous pigment and dye ink compatible
- Excellent colour gamut and exceptional d-max
- Instant dry

Applications

- Fine art and photographic open and limited edition prints
- Fine art and fine photographic reproduction and restoration
- · Art and photo portfolios
- Greeting cards and postcards

| Basic Weight (gsm) | 285 | | |
|---------------------------|--|---|-------|
| Paper Thickness (Microns) | 285 | Paper Thickness (Inches) | 0.011 |
| Base Material | Alpha Cellulose | | |
| Coating Type | Microporous Gloss | | |
| Surface Texture | Ultra Smooth | | |
| Whiteness (CIE) | 152 | | |
| Brightness (TAPPI) | 111 | | |
| OBA Content | Yes | | |
| рН | 7.5-9.5 | | |
| Recyclable | Yes | | |
| Print Settings* | PK Ink, Gloss or Semi Gloss Photo Paper Settings are recommended as a starting point | | |
| Notes | FibaPrint® glossy papers mark more easily, it is recommended to wear cotton gloves when handling | | |
| | *6 . | ICC Duafia a fau a ala eta el muinta uma a el ala | |

*Generic ICC Profiles for selected printer models are available from the Innova Art website.

| Sheets | A4, A3, A3+, A2, 8.5x11", 11x17", 13x19", 17x22" | |
|--------------------|--|--|
| Rolls (15m Length) | 60", 44", 36", 24", 17" | |

Additional Sizes are available on request, subject to order quantity.

Handling and Storage

- All digital Fine Art Papers and Canvases are fragile and need to be handled with extreme care. Try not to touch the surface of the paper, always hold the paper by the edges and wear cotton gloves if necessary.
- Return unused material to the original box and only store finished prints in archival quality packaging. If mounting or framing, use only archive grade tapes and glues.
- After printing, leave prints open to the air to fully dry (24 hours is recommended). Do not stack prints on top of each other straight away.
- Using a giclée varnish or spray will help protect your print from damage, effects of UV light and environmental attack.

Conditions of Use

- The recommended climate for storage of all papers is 15-20°C, relative humidity of 40-60%. Always store in original packaging, out of direct sunlight and protected from moisture.
- Do not exceed temperatures of 82°C (180°F) when dry mounting.

All recommendations are for your guidance only. These are subject to our test criteria, which remain subject to change without prior notice.

