



Protection Tissue

ProTex[™] tissue's high density, neutral ph and formaldehyde-free composition provides the highest yield and the strongest barrier protection possible. Its heat resistant features extend the life of the calender belt by preventing surplus dye-sub gas from contaminating the belt of the rotary calender press. With more widths and diameters in stock, we have you covered!

FEATURES AND BENEFITS:

Longer roll lengths

Fewer roll changes, less downtime.

Lower basis weight

Reduces purchase transport, storage, and disposal costs.

Natural color

No bleaching agents, less harmful to the environment.

Formaldehyde-free

Eliminates a major cause of heat induced textile yellowing.

High gas barrier sheet with heat resistance

Extends the life of the calender belt by blocking excess dye-gas.

Neutral ph

Retains most tensile strength after prolonged exposure to heat.

Recyclable

100% recyclable ingredients.

High tensile strength

Reduces web tear-outs.

APPLICATIONS:

> All heat press calender transfers



| ProTex [™] Protection Tissue Properties | | | | |
|--|------------|-----------|-----------|-----------|
| Properties | ProTex 19 | | ProTex 25 | |
| Basis Weight | 19 gsm | | 25 gsm | |
| Thickness | 31.2 μm | | 44.5 μm | |
| Thermal Transfer Tissue Approx. Weight Per Roll | | | | |
| 11.5 Pound (19 Gram) | | | | |
| | 16" | 12" | 10" | 8″ |
| Roll Widths | Diameter | Diameter | Diameter | Diameter |
| 36" (.914 m) | 186 lbs. | 97 lbs. | 69 lbs. | 38 lbs. |
| 40" (1.01 m) | 207 lbs. | 107 lbs. | 77 lbs. | 42 lbs. |
| 48" (1.21 m) | 248 lbs. | 129 lbs. | 92 lbs. | 51 lbs. |
| 54" (1.37 m) | 279 lbs. | 145 lbs. | 104 lbs. | 57 lbs. |
| 60" (1.55 m) | 311 lbs. | 161 lbs. | 115 lbs. | 63 lbs. |
| 64" (1.63 m) | 331 lbs. | 172 lbs. | 123 lbs. | 68 lbs. |
| 66" (1.67 m) | 342 lbs. | 177 lbs. | 127 lbs. | 70 lbs. |
| 68" (1.72 m) | 351 lbs. | 182 lbs. | 130 lbs. | 72 lbs. |
| 72" (1.83 m) | 373 lbs. | 193 lbs. | 138 lbs. | 76 lbs. |
| 80" (2.03 m) | 414 lbs. | 214 lbs. | 153 lbs. | 84 lbs. |
| 96" (2.43 m) | 497 lbs. | 258 lbs. | 184 lbs. | 101 lbs. |
| 104" (2.64 m) | 538 lbs. | 278 lbs. | 199 lbs. | 110 lbs. |
| Yards per roll | 5400 yds. | 2800 yds. | 2000 yds. | 1100 yds. |
| Feet per roll | 16,200 ft. | 8400 ft. | 6000 ft. | 3300 ft. |
| 15 Pound (25 Gram) | | | | |
| | 16" | 12" | 10" | 8″ |
| Roll Widths | Diameter | Diameter | Diameter | Diameter |
| 126" (3.2 m) | 661 lbs. | 347 lbs. | 244 lbs. | 126 lbs. |
| 130" (3.3 m) | 680 lbs. | 356 lbs. | 251 lbs. | 129 lbs. |
| Yards per roll | 4200 yds. | 2200 yds. | 1550 yds. | 800 yds. |
| Feet per roll | 12,600 ft. | 6600 ft. | 4650 ft. | 2400 ft. |

Beaver Paper

2420 Tech Center Parkway, Bldg. 140 Lawrenceville, GA 30043 USA

Contact Customer Service & Sales: +1 770-935-5080 x1 orders@beaverpaper.com or info@beaverpaper.com

Beaver Paper GmbH

Im Lossenfeld 19 77731 Willstätt, Germany

Contact Customer Service info@beaverpaper.com customerservices@beaverpaper.de